

Erratum to: Electrochemical Frequency Modulation: Solution Resistance and Double Layer Capacitance Considerations

Shashi Lalvani^{1,†}, Sifat Ullah², and Lei Kerr¹

¹Chemical, Paper and Biomedical Engineering, Miami University, Oxford, Ohio 45056

²Mechanical and Manufacturing Engineering, Miami University, Oxford, Ohio 45056

Erratum to: CORROSION SCIENCE AND TECHNOLOGY, Vol. 20, No. 5(2021), pp.231~241
DOI: <https://doi.org/10.14773/cst.2021.20.5.231>

Following the authors' request, there is a change in the equation.

Correction

p. 233

$$\frac{dE}{dt} + \frac{i_{corr}}{c_d} \left[e^{\frac{E-E_{corr}}{\beta_a}} - e^{-\frac{-(E-E_{corr})}{\beta_c}} \right] + \frac{E}{R_s c_d} = \frac{E}{R_s c_d} + \frac{1}{R_s c_d} [E_{p1} \sin(\omega_1 t) + E_{p2} \sin(\omega_2 t)] \quad (6)$$

to

$$\frac{dE}{dt} + \frac{i_{corr}}{c_d} \left[e^{\frac{E-E_{corr}}{\beta_a}} - e^{-\frac{-(E-E_{corr})}{\beta_c}} \right] + \frac{E}{R_s c_d} = \frac{E_{DC}}{R_s c_d} + \frac{1}{R_s c_d} [E_{p1} \sin(\omega_1 t) + E_{p2} \sin(\omega_2 t)] \quad (6)$$